



1. MATERIAL:
 - Antenna Cover:TPEE
 - Antenna Base:PC+PBT
 - Color:Black
 - Operating Temperature: $-20^{\circ}\text{C} \sim +65^{\circ}\text{C}$
 - Storage Temperature: $-30^{\circ}\text{C} \sim +75^{\circ}\text{C}$
 - CABLE:MI-113
 - Connector:IPEX
 - Cable Length:(option)
2. ELECTRICAL
 - Frequency:2.4G/5.8G(DUALBAND)
 - Impedance:50Ω
 - VSWR ≤ 2.0
 - Gain:2.4GHz 1.5dBi, 5.8GHz 2.5dBi
 - Radiation:0 mni
 - Electronic Wave:1/4λ,Dipole
 - Polarization: Vertical
3. UNSPECIFIED TOLERANCE: .X ±0.50[0.011]

RoHS Compliant

X MULTIPLE		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE:		DWG NO:	
Ø9 DUALBAND ANTENNA FOR IPEX		XANT-A003-B5002	
PART NO:		DRAWN:	
XANT-A003-B5002		LEON	
 		CHKD:	
UNIT	SHEET	REV	
mm[inch]	1 of 1	01	
		DATE:	
		May.08,08	