



1. MATERIAL:
 - Antenna Cover:PU
 - Antenna Base:PU UL 94V-0
 - Color:Black
 - Operating Temperature:-20° C~+65° C
 - Storage Temperature:-30° C~+75° C
 - SMA Connector(Optional):MALE PIN OR FEMALE PIN
2. ELECTRICAL
 - Frequency:2.4G/5.8G(DUALBAND)
 - Impedance:50Ω
 - VSWR ≤2.0
 - Gain:2.4GHz 1.5dBi, 5.8GHz 2.5dBi
 - Radiation:0 mni
 - Electronic Wave:1/4 λ ,Dipole
 - Polarization: Vertical
3. UNSPECIFIED TOLERANCE: .X ±0.50[0.011]

RoHS Compliant

X MULTIPLE		THE INFORMATION AGE	
<small>XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475</small>		<small>XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065</small>	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: PART NAME Ø10 DUALBAND ANTENNA FOR SMA		DWG NO: XANT-A003-B5003	
PART NO: XANT-A003-B5003		DRAWN: LEON	
		CHKD: TARA	
		DATE: May.08,08	
UNIT mm[inch]	SHEET 1 of 1	REV 01	