




1. MATERIAL:
  - Antenna Cover:PU
  - Antenna Base:PC UL 94V-0
  - Color:Black
  - Operating Temperature:-20° C~+65° C
  - Storage Temperature:-30° C~+75° C
  - CABLE:MI-113
  - Connector:IPEX
  - Cable Length(option)
2. ELECTRICAL
  - Frequency:2.4G/5.8G(DUALBAND)
  - Impedance:50Ω
  - VSWR ≤2.0
  - Gain:2.4GHz 1.5dBi, 5.8GHz 2.5dBi
  - Radiation:0 mni
  - Electronic Wave:1/4 λ,Dipole
  - Polarization: Vertical
3. UNSPECIFIED TOLERANCE:
  - .X ±0.50[0.011]

RoHS Compliant

		<small>THE INFORMATION AGE</small>	
<small>XMULTIPLE ASIA 4F, No. 347,Yang Guang St., Neihu , Taipei , Taiwan 11475</small>		<small>XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065</small>	
<small>G/NO:</small>		<small>DWG NO:</small>	
<small>THIS DRAWING IS A CONTROLLED DOCUMENT.</small>		<small>XANT-A003-B5004</small>	
<small>TITLE:</small>		<small>DRAWN:</small>	
<small>φ13(132MM) DUALBAND ANTENNA FOR IPEX</small>		<small>LEON</small>	
<small>PART NO:</small>		<small>CHKD:</small>	
<small>XANT-A003-B5004</small>		<small>TARA</small>	
		<small>UNIT</small>	<small>SHEET</small>
		<small>mm[inch]</small>	<small>1 of 1</small>
		<small>REV</small>	<small>DATE:</small>
		<small>01</small>	<small>May.08,08</small>