



1. MATERIAL:  
 Antenna Cover:PU  
 Antenna Base:PC UL 94V-0  
 Color:Black  
 Operating Temperature:-20° C~+65° C  
 Storage Temperature:-30° C~+75° C  
 SMA Connector(OPTION):MALE PIN OR FEMALE PIN
2. ELECTRICAL  
 Frequency:2.4G/5.8G(DUALBAND)  
 Impedance:50Ω  
 VSWR ≤2.0  
 Gain:2.4GHz 1.5dBi, 5.8GHz 2.5dBi  
 Radiation:0 mni  
 Electronic Wave:1/4λ,Dipole  
 Polarization: Vertical
3. UNSPECIFIED TOLERANCE: .X ±0.50[0.011]

RoHS Compliant

<b>X</b> MULTIPLE		THE INFORMATION AGE	
<small>XMULTIPLE ASIA 4F, No. 347,Yang Guang St., Neihu , Taipei , Taiwan 11475</small>		<small>XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065</small>	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: φ13(132MM) DUALBAND ANTENNA FOR SMA		DWG NO: XANT-A003-B5005	
PART NO: XANT-A003-B5005		DRAWN: LEON	
		CHKD: TARA	
		DATE: May.08,08	
UNIT mm[inch]	SHEET 1 of 1	REV 01	