

XRJS/XMS RJ45 SMT CONNECTORS

FEATURES:

- RJ45 Surface Mount Connectors
- Available in 1, 2 and 4 Ports
- Available With and Without Magnetics
- SMT Contacts
- Available with or without LEDs for Easy Viewing of Connection/Activity Status
- Available in Shield or Unshielded
- Minimum of 750 to 1000 Insertion Cycles
- Applications Include: Desktop PC, Server, Hub, Switch, LCD TV, STB, Amplifier, AV Center, POS, Printer, Projector, Camera Systems



GENERAL SPECIFICATION:

Product Type Features		Housing Related Features	
Tab Type	Tab Up and Tab Down	Material	PBT / Nylon / LCP
PCB Mount Angle	SMT	Housing Flammability	UL 94V-0
Number of Ports	1, 2 and 4 Ports	Color	Optional
Number of Positions	8	Contact Features	
Number of Contacts	Optional	Material	Phos-Bronze
LED	With or Without	Contact Area Plating	Hard Gold
Transformer	With and Without	Solder Area Plating	Tin/Gold Flash
Shielding Features		Magnetic Features	
Material	Copper Alloy	Transformer Speed	10/100/1000 Mbps
Plating	Nickel		
EMI Fingers	With or Without		
Number of PCB Ground Tabs	2 and 4		
Ground Pin Position (mm)	Optional		

ORDERING INFORMATION:

PART NO. X	PORT NO. X	Length X	Width X	Height X
XRJS/XMS-S-01-8-8-X	1 Port	Optional	Optional	Optional
XRJS/XMS-S-02-8-8-X	2 Port	Optional	Optional	Optional
XRJS/XMS-S-04-8-8-X	4 Port	Optional	Optional	Optional