



NOTES:

- CABLE
UL 20276 (28AWG*1P+DRAIN+AL MYLOR)*4
+28AWG*1P+28AWG*5C+AI FOIL+BRAID, OD=6.0mm,
JACKET COLOR : BLACK.
- CONN 1
HDMI 19P MALE.
INSULATION: LCP UL94V-0 COLOR : BLACK
CONTACT: COPPER ALLOY, WITH GOLD PLATING
SHELL: ZINC ALLOY WITH NICKEL PLATING
- CONN 2
DVI 18+KEY MALE .
INSULATION: PBT UL 94V-0 COLOR : WHITE
CONTACT: COPPER ALLOY, WITH GOLD PLATING
SHELL: STEEL WITH NICKEL PLATING
- SCREW 4-40#
- PERFORMANCE CHARACTERISTICS:
DIELECTRIC WITHSTANDING VOLTAGE: 300VDC FOR 10MS.
CONDUCTANCE RESISTANCE: 5 OHM MAX.
INSULATION RESISTANCE: 5M OHM MIN
- UNSPECIFIED TOLERANCE: .X ±0.30

CONN 1	COLOR OF CABLE	CONN 2
1	WHITE/RED	2
3	WHITE	1
2	DRAIN	3
4	WHITE/GREEN	10
6	WHITE	9
5	DRAIN	11
7	WHITE/BLUE	18
9	WHITE	17
8	DRAIN	19
10	WHITE/BLACK	23
12	WHITE	24
11	DRAIN	22
15	ORANGE	6
16	YELLOW	7
17	RED	15
18	GREEN	14
19	BLUE	16
13	NC	
14	NC	
SHELL	BRAID	SHELL

X MULTIPLE		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475		XMULTIPLE USA 543 Country Club Drive #B 128 Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		CUSTOMER/NO:	
TITLE: CABLE - HDMI(M) TO DVI(M)		DWG NO: XHDMI-C1-021-L	
PART NO: XHDMI-C1-021-L		DRAWN: TARA	
		CHKD: JEFF	
		DIMENSIONS	SHEET
mm[inch]		1 of 1	REV
		01	DATE: 10/12/04