



P.C.B LAYOUT

UNSPECIFIED TOLERANCE : .XX  $\pm 0.20[0.008]$   
 .X  $\pm 0.30[0.012]$

RoHS Compliant

LTR	PART NAME	MATERIAL	DESCRIPTION	QTY
1	HOUSING	NY-6T UL94V-0	COLOR-BLACK 260°C for 10 Seconds Initial: 1000M Ohms Min. After Test: 500M Ohms Min.	1
2	CONTACT	BRASS C2680	Plating Gold Flash Current Rating: 3.0A Initial: 20m Ohms Max. After Test: 40m Ohms Max.	6

NORMAL FORCE: 800 GRAMS AVERAGE  
 TEMPERATURE RATING : -40°C ~ +125°C  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC/MIN

<b>X MULTIPLE</b>		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: PITCH 2.54*2.54 mm PIN HEADER STRAIGHT DUAL ROWS		DWG NO: XPHD-M203D-001	
PART NO: XPHD-M203D-001		DRAWN: TOM	
		UNIT	REV
		mm[inch]	01
SHEET		DATE:	
1 of 1		TARA Mar.15,09	