


SPECIFICATION:  
 CURRENT RATING: 0.5 A MAX  
 VOLTAGE RATING: 40 V AC(RMS) MAX  
 CONTACT RESISTANCE: 50 MΩ MAX  
 DIELECTRIC WITHSTANDING VOLTAGE: 100 V(AC) FOR 1 MIN  
 INSULATION RESISTANCE: 1000 MΩ MIN  
 OPERATION TEMPERATURE RANGE: -25°C~85°C  
 UNSPECIFIED TOLERANCE: .XX ±0.20[0.008]  
 .X ±0.25[0.010]

RoHS Compliant

5	PCB	COLOR: GREEN.	1.60mm	1
4	CONTACT	PHORPHOR BRONZE, PLATED WITH 15u' GOLD	0.30mm	19
3	INSULATOR-B	PA6T+30%GF, UL94V-0		1
2	SHELL	BRASS	0.40MM	1
1	INSULATOR-F	PBT+30%GF, UL94V-0		1
No.	PART NAME	DESCRIPTION	THICKNESS	Q'TY

**X MULTIPLE** THE INFORMATION AGE

XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065		G/NO:
THIS DRAWING IS A CONTROLLED DOCUMENT.				DWG NO:
TITLE: HDMI 19PIN (F) Edge Mounted Type (PCB)				XHDMI-F19C0-01-0W
PART NO: XHDMI-F19C0-01-0W				DRAWN:
				TOM
				CHKD:
				TARA
				DATE:
				Sep.30,08



UNIT	SHEET	REV
mm[inch]	1 of 1	02