



Recommend P.C.B Layout

NOTE:

- 1.MATERIAL:
 - 1-1.HOUSING: LCP.
 - 1-2.CONTACT: BRONZE.
 - 1-3.SHELL: BRASS.
- 2.PLATING:
 - 2-1.CONTACT: CONTACT AREA 15u" GOLD , AND SOLDER AREA GOLD FLASH. UNDER NICKEL 50u"MIN.
 - 2-2.SHELL: NICKEL 60u" MIN.
- 3.SAFETY:
 - 3-1.CONTACT RESISTANCE: CONTACT 30mohm MAX. SHELL 50mohm MAX.
 - 3-2.INSULATION RESISTANCE: UNMATED100mohm MIN. MATED 10Mohm MIN.
 - 3-3.DIELECTRIC STRENGTH: 500 Vac MIN.
 - 3-4.CURRENT RATING: 0.5A MIN.
4. UNSPECIFIED TOLERANCE: .XX ±0.20[0.008]
.X ±0.25[0.010]

RoHS Compliant

X MULTIPLE		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: MINI HDMI 19 PIN (F) C TYPE DIMINI P		DWG NO: XHDMI-F19M0-01-MT	
PART NO: XHDMI-F19M0-01-MT		DRAWN: IVAN	
		UNIT	REV
		mm[inch]	01
SHEET		DATE:	
1 of 1		Feb.23,09	