



SUGGESTED PCB LAYOUT  
TOP VIEW  
DIMENSIONAL TOLERANCE: .XX ±0.08[0.003]

SPECIFICATION:

CURRENT RATING: 0.5 A MAX  
 VOLTAGE RATING: 40 V AC(RMS) MAX  
 CONTACT RESISTANCE: 50 MΩ MAX  
 DIELECTRIC WITHSTANDING VOLTAGE: 100 V(AC) FOR 1 MIN  
 INSULATION RESISTANCE: 1000 MΩ MIN  
 OPERATION TEMPERATURE RANGE: -25°C~85°C  
 UNSPECIFIED TOLERANCE: .XX ±0.20[0.008]  
 .X ±0.25[0.010]

RoHS Compliant

<b>X MULTIPLE</b>		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: HDMI 19PIN (M) EDGE MOUNT TYPE (PCB)		DWG NO: XHDMI-M19C0-01-0W	
PART NO: XHDMI-M19C0-01-0W		DRAWN: TOM	
		CHKD: JEFF	
		DATE: Jul,19,07	
UNIT	SHEET	REV	
mm[inch]	1 of 1	01	

2	P.C.B BROAD, THICKNESS: 1.6MM, COLOR: GREEN	1
1	HDMI 19PIN, PLATED WITH 15u" GOLD, MALE EDGE MOUNT TYPE	1
No.	DESCRIPTION	Q'TY