


SPECIFICATION
 1. Rating :DC 30V 0.5A;
 2. Contact resistance: ≤0.03Ω;
 3. Insulation resistance: ≥100MΩ (DC250V);
 4. Withstand voltage: 500VAC;
 5. Insertion and extraction force: -20N;
 6. life test: 00 cycles.

SCHMATIC



6	COVER	1	PBT	
5	HOUSING	1	PBT	
4	FLAT PIECE	1	H62 BRASS	Ag-Plating
3	SPRING	1	BRONZE	Ag-Plating
2	CURVE PIECE	1	H62 BRASS	Ag-Plating
1	PIN	1	H59 BRASS	Ni-Plating
NO.	DESCRIPTION		MATERIAL	PLATING

<h1>X MULTIPLE</h1>		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475		XMULTIPLE USA 1402 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		CUSTOMER/NO:	
TITLE: DC-JACK		DWG NO: XDCP-DC-005D	
PART NO: XDCP-DC-005D		DRAWN: LEON	
		CHKD: JEFF	
	DIMENSIONS	SHEET	REV
mm[inch]	1	of 1	02
		DATE: 03/05/05	