



PCB LAYOUT
Ref.

☆	CODE	LED 2 [LEFT]	LED 1 [RIGHT]
	0	BLOCKED	BLOCKED
	1	YELLOW	GREEN
	2	BLOCKED	GREEN
	3	YELLOW	BLOCKED
	4	GREEN	YELLOW
	5	GREEN	GREEN
	6	YELLOW	YELLOW
	7	OR/GR	OR/GR
	8	YE/GR	YE/GR
	9	OR/GR	YELLOW

NOTES:

- MATERIAL:**
 △ HOUSING—PBT POLYESTER UL-94V-0
 MIXED GLASS FIBER.
 STANDARD COLOR—BLACK
 CONTACTS—0.35mm THICK PHOS—BRONZE PLATED
 WITH 30u" HARD GOLD AND TIN/LEAD IN
 SOLDER AREA.
 SHIELD—0.20mm THICK COPPER ALLOY,
 PLATED WITH 50u" Ni
 (50% SHINE SOLVENT)

- ELECTRICAL:**
 CONTACT RESISTANCE: 20 MILLIOHMS MAXIMUM
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM
 CURRENT RATING: 1.5 AMPS
 VOLTAGE RATING: 150 VOLTS AC
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
 PART 68, SUBPART F.
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
 .X ±0.30[0.012]

CONNECTING THE INFORMATION AGE

XMULTIPLE ASIA 4F, No. 347, Yang Sung St., Neihu Chiu, Taipei, Taiwan 11475	XMULTIPLE USA 643 Country Club Drive #8 128 Simi Valley, CA 93065	CUSTOMER/NO:
THIS DRAWING IS A CONTROLLED DOCUMENT.		
TITLE: Stacked RJ45, W/LED, with 10/100/1000 Mbps Filter BP, 10C, Shielded, Thru Hole.		DWG NO: XRJH-12-24-8-A-X-901
PART NO: XRJH-12-24-8-A-X-901		DRAWN: TARA
		CHKD: FUTJEN
DIMENSIONS mm[inch]		SHEET 1 of 2
		REV 02
		DATE: 02/10/03*

