


SUGGESTED PCB LAYOUT TOLERANCE
 .XX±0.05[0.002]

NOTES:

- MATERIALS:
 HOUSING-PBT POLYESTER UL94V-0
 MIXED GLASS FIBER.
 STANDARD COLOR-BLACK
 CONTACTS-0.45mm DIA. ROUND PHOS-BRONZE
 PLATED WITH 50u" GOLD.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
 PART 68,SUBPART F.
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
 .X ±0.30[0.012]



	CODE	LED 2 [LEFT]	LED 1 [RIGHT]
☆	0	BLOCKED	BLOCKED
	1	YELLOW	GREEN
	2	BLOCKED	GREEN
	3	YELLOW	BLOCKED
	4	GREEN	YELLOW
	5	GREEN	GREEN
	6	YELLOW	YELLOW
	7	OR/GR	OR/GR
	8	YE/GR	YE/GR
	9	OR/GR	YELLOW

<h1>X MULTIPLE</h1>		CONNECTING THE INFORMATION AGE	
X MULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475		X MULTIPLE USA 543 Country Club Drive #B 128 Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		CUSTOMER/NO: 9636-4413-A	
TITLE: RJ11 Connectors, W/O LED, 4P, 4C, Unshielded, Thru-Hole		DWG NO: XRJK-U-01-4-4-0-904	
PART NO: XRJK-U-01-4-4-0-904		DRAWN: JEFF	
		CHKD: Futien	
		DATE: 02/12/03	
DIMENSIONS		SHEET	REV
mm[inch]		1 of 1	01