



	CODE	LED 2 [LEFT]	LED 1 [RIGHT]
☆	0	BLOCKED	BLOCKED
	1	YELLOW	GREEN
	2	BLOCKED	GREEN
	3	YELLOW	BLOCKED
	4	GREEN	YELLOW
	5	GREEN	GREEN
	6	YELLOW	YELLOW
	7	OR/GR	OR/GR
	8	YE/GR	YE/GR
	9	OR/GR	YELLOW

NOTES:

1. MATERIAL:

- HOUSING-PBT POLYESTER UL-94V-0 MIXED GLASS FIBER. STANDARD COLOR-BLACK
- CONTACTS-0.35mm THICK PHOS-BRONZE PLATED WITH 6u" GOLD AND TIN/LEAD IN SOLDER AREA.

2. CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68,SUBPART F.

3. UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
.X ±0.30[0.012]

SUGGESTED PCB LAYOUT TOLERANCE .XX±0.05[0.002]

CONNECTING THE INFORMATION AGE

XMULTIPLE ASIA 4F, No. 347 Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475	XMULTIPLE USA 543 Country Club Drive #B 128 Simi Valley, CA 93065	CUSTOMER/NO: 9740-8814
THIS DRAWING IS A CONTROLLED DOCUMENT.		
TITLE: RJ45 Connectors, w/O LED,8P,8C, Unshielded, Thru-Hole		
PART NO: XRJK-U-01-8-8-0-909		DWG NO: XRJK-U-01-8-8-0-909
		DRAWN: TARA
DIMENSIONS mm[inch]		SHEET 1 of 1
DATE: 05/12/03		CHKD: C. TSAI
REV 01		