



BI-COLOR LED DETAIL  
(RED, RED/YELLOW, GREEN/ORANGE LED'S ARE ALSO AVAILABLE)

PCB LAYOUT  
TOLERANCE  
.XX±0.05[0.002]

1. MATERIALS:  
HOUSING: HIGH TEMP. THERMOPLASTIC, BLACK, UL 94V-0  
CONTACTS: 0.014 INCHES (0.35 MILLIMETERS) THICK PHOSPHOR BRONZE PLATED WITH 150 MICROINCHES (3.81 MICROMETERS) MINIMUM THICK TIN LEAD IN SOLDER AREA. 15 MICROINCHES (0.38 MICROMETERS) MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 50 MICROINCHES (1.27 MICROMETERS) MINIMUM THICK NICKEL.

2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F  
3. PART NUMBER: XRJ-U-01-8-B-X-F1

REFER TO LED OPTIONS TABLE FOR ORDERING CODES

NOTES:

UNLESS OTHERWISE SPECIFIED  
UNSPECIFIED TOLERANCE: .XX±0.25[0.010]  
.X±0.30[0.012]

XMULTIPLE		CONNECTING THE INFORMATION AGE
XMULTIPLE AREA 5F, No. 80, Hsinchu St. Tainan, 704, Taiwan, R.O.C.	XMULTIPLE USA 3008 Old County Road Newbury Park, CA 91380	END:
THIS DRAWING IS A CONTROLLED DOCUMENT.		DRWNO: PDU02-801
TITLE: RJ45, Connectors, W/LED, 8P, BC, UNSHIELDED, Thru-Hole		DRWNG: VIQ
PART NO: XRJM-U-02-8-B-X-F1		DRW: C. TSAI
	DIMENSIONS	SHEET
	mm[inch]	1 of 1
	REV	DATE
	J	10/06/01