



PCB LAYOUT TOLERANCE  
SUGGESTED PCB LAYOUT .XX±0.05[0.002]

NOTES:

- MATERIAL:  
HOUSING—DSM STANYL TE250FB (NYLON-46)  
HEAT DEFLECTION TEMP.290°  
BLACK COLOR, UL94V-0  
CONTACTS—0.35mm THICK PHOS-BRONZE PLATED WITH HARD GOLD AND TIN/LEAD IN SOLDER AREA.  
SHIELD—0.25mm THICK COPPER ALLOY, PLATED WITH NICKEL.
- ELECTRICAL  
INSULATION RESISTANCE : 500 MEGOHMS MINIMUM  
CURRENT RATING : 1.5 AMPS  
VOLTAGE RATING : 150 VOLTS AC
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68,SUBPART F.
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]  
.X ±0.30[0.012]

	CODE	LED 2 [LEFT]	LED 1 [RIGHT]
☆	0	BLOCKED	BLOCKED
	1	YELLOW	GREEN
	2	BLOCKED	GREEN
	3	YELLOW	BLOCKED
	4	GREEN	YELLOW
	5	GREEN	GREEN
	6	YELLOW	YELLOW
	7	OR/GR	OR/GR
	8	YE/GR	YE/GR
	9	OR/GR	YELLOW

**X MULTIPLE**

CONNECTING THE INFORMATION AGE

XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Dist., Taipei, Taiwan 11475		XMULTIPLE USA 243 Country Club Drive #B 12B Simi Valley, CA 93065		CUSTOMER/NO: 8714-8813-483-B
THIS DRAWING IS A CONTROLLED DOCUMENT.				DWG NO: XRJM-S-04-8-8-0-901
TITLE: RJ45, Connectors, W/a LED, 8P, 8C, Shielded, Thru-Hole				
PART NO: XRJM-S-04-8-8-0-901		DRAWN: TARA		
		CHKD: FUTIEN		
		DIMENSIONS mm[inch]	SHEET 1 of 1	REV 01
		DATE: 18/08/03		