



PCB LAYOUT
Ref.

- NOTES:
- MATERIALS:
HOUSING-DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR,UL94V-0
CONTACTS-0.35mm THICK PHOS-BRONZE PLATED WITH 15u" GOLD,AND GOLD FLASH IN ALL AREA,EXCEPT CUT AREA.
SHIELD -0.25mm THICK COPPER ALLOY, PLATED WITH Ni.
 - CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68,SUBPART F.
 - OPERATING TEMPERATURE:-40°C TO +85°C
 - UNSPECIFIED TOLERANCE: .XX ±0.25
.X ±0.30

RoHS Compliant

XMULTIPLE		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
G/NO:		DWG NO:	
THIS DRAWING IS A CONTROLLED DOCUMENT.		XRJS-S-01-8-8-1-901-LF	
TITLE: RJ45 Connectors, W/LED,8P,8C, Shielded, SMT TYPE, LEAD FREE, CAT.5		DRAWN: TARA	
PART NO: XRJS-S-01-8-8-1-901-LF		CHKD: JEFF	
		DIMENSIONS mm[inch]	SHEET 1 of 1
		REV 01	DATE: 18/01/05