



SUGGESTED PCB LAYOUT
TOP VIEW
DIMENSIONAL TOLERANCE: .XX ±0.08[0.003]

XUSB-7-2-4-3-1-1-04

7 : MINI USB
2 : SMT TYPE
NUMBER OF PIN
SHELL PLATING
3 : ALL NI

4 : SERIAL NUMBER
HOUSING COLOR
1 : BLACK
PIN PLATING
1 : GOLD FLASH

RoHS Compliant

- NOTE:
- SAFETY:
 - 1-1 RATING: DC 30V/2A
 - 1-2 CONTACT RESISTANCE: 30M OHM OR LESS
 - 1-3 INSULATION RESISTANCE: 500M OHM MIN AT DC100V
 - 1-4 DIELECTRIC WITHSTANDING VOLTAGE: AC 250V FOR 1 MINUTE
 - MATERIAL:
 - 2-1 PIN: PHOSPHOR BRONZE
 - 2-2 HOUSIG: NYLON, BLACK
 - 2-3 SHELL: STAINLESS STEEL
 - PLATING:
 - 3-1 PIN: GOLD FLASH
 - 3-2 SHELL: NICKEL
 - UNSPECIFIED TOLERANCE: .XX ±0.25
.X ±0.30

		THE INFORMATION AGE			
				XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475	XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065
THIS DRAWING IS A CONTROLLED DOCUMENT.				DWG NO:	
TITLE: MINI USB 4PIN FEMALE			XUSB-7-2-4-3-1-1-04		
PART NO: XUSB-7-2-4-3-1-1-04			RUNES CHKD:		
		UNIT mm[inch]	SHEET 1 of 1	REV 01	DATE: Mar.13,07