



NOTE:

- RJ45 PLUG TERMINAL GOLD 6U"  
ELECTRICAL:  
VOLTAGE RATING:125 VAC RMS.  
CURRENT RATING:1.5 AMP  
CONTACT RESISTANCE: 30 MILLIOHMS MAX.  
INSULATION RESISTANCEV:1000 MEGOHMS MIN @ 500 VDC  
DIELECTRIC STRENGTH:1000 VAC RMS 60Hz 1MIN
- USB AM SMT TYPE GOLD 3U"  
ELECTRICAL CHARACTERISTICS:  
CONTACT RESISTANCE:30M OHMS MAX  
INSULATION RESISTANCE:100M OHMS MIN  
DIELECTIRC WITHSTANDING VOLTAGE:500V DC AT 1 MINUTE

<b>X MULTIPLE</b>		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yong Guang St., Neihu Chiu, Taipei, Taiwan 11475.		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE: USB TO RJ45		G/NO:	
PART NO: XADT-1P04-0-6S08-001		DWG NO: XADT-1P04-0-6S08-001	
		DRAWN: LEON	
		CHKD: JEFF	
		DATE: 16/08/05	
		DIMENSIONS	SHEET
		mm	1 of 1
		REV	01