



NOTE:

1. RJ45 PLUG TERMINAL GOLD 3U"
ELECTRICAL:
VOLTAGE RATING:125 VAC RMS.
CURRENT RATING:1.5 AMP
CONTACT RESISTANCE: 45 MILLIOHMS MAX.
INSULATION RESISTANCE:1000 MEGOHMS MIN @ 500 VDC
DIELECTRIC STRENGTH:1000 VAC RMS 60Hz 1MIN
2. USB2.0 AM SMT TYPE GOLD 30U"
ELECTRICAL CHARACTERISTICS:
CONTACT RESISTANCE:30M OHMS MAX
INSULATION RESISTANCE:100M OHMS MIN
DIELECTRIC WITHSTANDING VOLTAGE:500V DC AT 1 MINUTE

X MULTIPLE		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475.		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE: USB TO RJ45		G/NO:	
PART NO: XADT-1P04-0-6S08-002		DWG NO: XADT-1P04-0-6S08-002	
		DRAWN: LEON	
		CHKD: JEFF	
		DIMENSIONS	SHEET
		mm	1 of 1
		REV	DATE
		01	16/08/05