

RECOMMEND  
P.C.B. THK  
=1.0~1.8mm

SUGGESTED PCB LAYOUT  
(TOP VIEW)  
DIMENSIONAL TOLERANCE: .XX ±0.08[0.003]

NOTES:



- ELECTRICAL CHARACTERISTICS:  
CONTACT CURRENT RATING: 3AMPERES.  
DIELECTRIC WITHSTANDING VOLTAGE: AC 500V AT SEA LEVEL.  
INSULATION RESISTANCE: 1000MEGΩHMS MIN.  
CONTACT RESISTANCE: 30MILLIOHMS MAX.  
OPERATING TEMPERATURE: -55°C TO +105°C
- MATERIALS:  
PLASTIC: PBT, BLACK COLOR  
CONTACT: COPPER ALLOY, PLATED WITH GOLD FLASH
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]  
.X ±0.30[0.012]

△ SHELL: SPCC, PLATED WITH NICKEL

XDSB-1-5-09-3-1-1-01

1: D-SUB  
5: RIGHT ANGLE DIP  
PIN No.  
SHELL PLATING  
3: ALL NI  
HOUSING COLOR  
1: BLACK  
PIN PLATING  
1: GOLD FLASH  
SERIAL NUMBER

RoHS Compliant

|   |  |  |                    |
|---|--|--|--------------------|
| X MULTIPLE  |  | THE INFORMATION AGE  |                    |
| <small>XMULTIPLE ASIA<br/>4F, No. 347, Yang Guang St.,<br/>Neihu, Taipei, Taiwan 11475</small>  |  | <small>XMULTIPLE USA<br/>1420 Los Angeles Ave., Suite G,<br/>Simi Valley, CA 93065</small> |                    |
| THIS DRAWING IS A CONTROLLED DOCUMENT.  |  | G/NO:  |                    |
| TITLE: DSUB 09M 90D DIP   |  | DWG NO:<br>XDSB-1-5-09-3-1-1-01  |                    |
| PART NO: XDSB-1-5-09-3-1-1-01   |  | DRAWN:<br>IVAN   |                    |
|   |  | UNIT<br>mm[inch]   | SHEET<br>1 of 1    |
|   |  | REV<br>02  | DATE:<br>Mar.19,09 |