



XDSB-1-5-09-3-1-1-06

1: D-SUB
5: RIGHT ANGLE DIP
PIN No.
SHELL PLATING
3: ALL NI

1: BLACK
HOUSING COLOR
PIN PLATING
1: GOLD FLASH
SERIAL NUMBER

NOTES:

- MATERIAL
INSULATOR: PBT, UL94V-0, BLACK
CONTACT: COPPER ALLOY, GOLD FLASH PLATED
SHELL: SPCC, NICKEL PLATED
- SPECIFICATION
CONTACT CURRENT RATING: 3 AMPERES
DIELECTRIC WITHSTANDING VOLTAGE: AC 1000/60sec.r.m.s.
INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM
CONTACT RESISTANCE: 25 MILLIOHMS MAXIMUM
- OPERATING TEMPERATURE: -55°C TO +105°C
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
.X ±0.30[0.012]

RoHS Compliant

X MULTIPLE		THE INFORMATION AGE	
X MULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		X MULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO: DWG NO: XDSB-1-5-09-3-1-1-06	
TITLE: D-SUB, 9 PINS, Right Angle		DRAWN: TOM	
PART NO: XDSB-1-5-09-3-1-1-06		CHKD: TARA	
		UNIT mm[inch]	SHEET 1 of 1
		REV 01	DATE: Sep.25,08