



NOTES:

- ELECTRICAL CHARACTERISTICS:  
 CONTACT CURRENT RATING: 5 AMPERES.  
 DIELECTRIC WITHSTANDING VOLTAGE: AC 1000/60SEC.R.M.S.  
 INSULATOR RESISTANCE: 1000 MEGOHMS MINIMUM  
 PIN RESISTANCE: 15 MILLIOHMS MAXIMUM.  
 OPERATING TEMPERATURE: -55°C TO +105°C.
- MATERIALS:  
 INSULATOR: PBT+FIBRE-GRASS, BLACK, UL 94V-0  
 CONTACT: COPPER ALLOY Au 15 MICRO-INCHS PLATED ON MATING  
 TIN 60 MICRO-INCHS MIN PLATED ON DIP-TAIL  
 NI 80 MICRO-INCHS MIN PLATED ON BASE SURFACE  
  
 BRACKET: STEEL, NICKEL PLATED  
 SPRING-WASHER: STEEL, NICKEL PLATED  
 JACK-SCREW: STEEL, NICKEL PLATED
- FINISHES:  
 CONTACT: GOLD FLASH  
 SHELL: NICKEL
- TEMPERATURE: -50°C ~ 100°C
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]  
 .X ±0.30[0.012]

RoHS Compliant

<b>X MULTIPLE</b>		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO: XDSB-1-5-64-3-5-1-01	
TITLE: CENTRONIC 64, FEMALE RIGHT-ANGLE PCB TYPE, WITH SCREW-LOCK		DWG NO: XDSB-1-5-64-3-5-1-01	
PART NO: XDSB-1-5-64-3-5-1-01		DRAWN: TARA	
		CHKD: JEFF	
		DATE: Mar.20,09	
UNIT mm[inch]	SHEET 1 of 1	REV 01	