



NOTES:

1. ELECTRICAL CHARACTERISTICS:
 Current Rating: 5 Amps
 Contact Resistance: 15 Milli-Ohms Max.
 Insulator Resistance: 1000 Meg-Ohms Min.
 Voltage: 500V RMS For 1 Minute
 OPERATING TEMPERATURE: -50°C TO +105°C.
2. MATERIALS:
 INSULATOR: PBT+30% Fibre-Grass, UL94-V0, color-blue
 CONTACT: Copper-Alloy, Au=15u" Min Plated,
 Nickel=50u" Min. Plated
 SHELL: STEEL, NICKEL PLATED
 AVERAGE MATING FORCE: 7.12 KG-F
 AVERAGE UNMATING FORCE: 6.85 KG-F
3. UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
 .X ±0.30[0.012]

RoHS Compliant

X MULTIPLE		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO: XDSB-1-5-64-3-5-1-02	
TITLE: CENTRONIC 64, PDS MALE, SOLDER-NESS IDC TYPE, WITH SCREW-LOCK		DRAWN: TOM	
PART NO: XDSB-1-5-64-3-5-1-02		CHKD: TARA	
		UNIT mm[inch]	SHEET 1 of 1
		REV 01	DATE: Mar.18,09