



NOTES:

1. THIS IS CONNECTOR TNC JACK FOR LMR-200.
2. ITEMS ④⑤ ARE SHIPPED UNASSEMBLED.
3. ELECTRICAL SPEC:
 - 3.1 IMPEDANCE: 50 OHMS NOMINAL.
 - 3.2 FREQUENCY RANGE: 0~6 GHZ.
 - 3.2 INSULATOR RESISTANCE: 1000 MEGOHMS MIN.
 - 3.2 WITHSTANDING VOLTAGE: 1000 VRMS.
 - 3.3 CONTACT RESISTANCE:
 - 3.3.1 CENTER CONTACT: 1.5 MILLIOHMS MAX.
 - 3.3.2 OUTER CONTACT: 1.0 MILLIOHMS MAX.
4. MECHANICAL SPEC:
 - 4.1 MATING: 7/16-28UNEF THREAD.
 - 4.2 DURABILITY: 500 CYCLES MIN.
5. UNSPECIFIED TOLERANCE: .XX ±0.25 [0.009]
.X ±0.30 [0.0118]

5	FERRULE	BRASS	NICKEL	1
4	SOCKET CONTACT	PHOSPHOR BRONZE	GOLD 0.08um MIN OVER NICKEL	1
3	GUIDE PIECE	BRASS	NICKEL	1
2	INSULATOR	PTFE	NONE	1
1	JACK BODY	BRASS	NICKEL	1
ITEM	NAME	SPEC.	FINISH	Q'TY

RoHS Compliant

		<small>THE INFORMATION AGE</small>	
<small>XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475</small>		<small>XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065</small>	
THIS DRAWING IS A CONTROLLED DOCUMENT.		<small>G/NO:</small>	
<small>TITLE:</small> TNC JACK		<small>DWG NO:</small> XRF-T1-2L2-CDA-K01	
<small>PART NO:</small> XRF-T1-2L2-CDA-K01		<small>DRAWN:</small> LEON	
		<small>CHKD:</small> JEFF	
<small>UNIT:</small> mm[inch]		<small>DATE:</small> Jan.25,08	
<small>SHEET:</small> 1 of 1		<small>REV:</small> 01	