



- NOTES:**
- MATERIALS:**
HOUSING: HIGH TEMP. THERMOPLASTIC, NYLON, UL 94V-0, BLACK.
CONTACTS: T=0.35 mm PHOSPHOR BRONZE, 50u" NICKEL UNDERPLATE
ON ALL AREA, 100u" TIN ON TERMINATION END,
15u" GOLD ON CONTACT AREA.
SHIELD: T=0.25 mm COPPER ZINC ALLOY PLATED WITH NICKEL
 - OPERATING TEMPERATURE:** -40°C ~ +85°C
 - JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F**
 - UNSPECIFIED TOLERANCE:** .XX ±0.25[0.010]
.X ±0.30[0.012]

RoHS Compliant

X MULTIPLE		<small>THE INFORMATION AGE</small>	
<small>MULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475</small>		<small>MULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065</small>	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO: DWG NO: XRJD-S-22-8-8-1-DE1-TEJ	
TITLE: Stacked RJ45 Connectors, w/LED, 8P,8C, Shielded, Thru Hole, 2 Piece Structure		DRAWN: TOM	
PART NO: XRJD-S-22-8-8-1-DE1-TEJ		CHKD: TARA	
UNIT mm[inch]		SHEET 1 of 1	
REV 01		DATE: Aug.04,08	