


SUGGESTED PCB LAYOUT  
PCB LAYOUT TOLERANCE  
.XX±0.05 [0.002]

XMULTIPLE Order Information

XRJD-S-23-8-8-4

Shielded Plating Type	
S	SHIELDED
U	Unshielded

LED COLOR OPTION  
NO. OF CONTACT  
NO. OF POSITION



	CODE	LED 2 [LEFT]	LED 1 [RIGHT]
	0	BLOCKED	BLOCKED
	1	YELLOW	GREEN
	2	BLOCKED	GREEN
	3	YELLOW	BLOCKED
☆	4	GREEN	YELLOW
	5	GREEN	GREEN
	6	YELLOW	YELLOW
	7	OR/GR	OR/GR
	8	YE/GR	YE/GR
	9	OR/GR	YELLOW
	Z	GR/OR	YELLOW

NOTES:

- MATERIALS:  
HOUSING: HIGH TEMP. THERMOPLASTIC, UL 94V-0, BLACK.  
CONTACTS: 0.014 INCHES (0.35 MILLIMETERS) THICK PHOSPHOR BRONZE PLATED WITH 150 MICROINCHES (3.81 MICROMETERS) MINIMUM THICK TIN LEAD IN SOLDER AREA. 15 MICROINCHES (0.38 MICROMETERS) MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 50 MICROINCHES (1.27 MICROMETERS) MINIMUM THICK NICKEL.  
SHIELDED: 0.0098 INCHES (0.25 MILLIMETERS) THICK COPPER ZINC ALLOY PLATED WITH 30 MICROINCHES (0.762 MICROMETERS) MINIMUM THICK NICKEL
- JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F
- PART NUMBER: XRJD-S-23-8-8-X  
REFER TO LED OPTIONS TABLE FOR ORDERING CODES
- UNSPECIFIED TOLERANCE: .XX ±0.25 [0.010]  
.X ±0.30 [0.012]

**XMULTIPLE**

CONNECTING THE INFORMATION AGE

XMULTIPLE ASIA 4F, No. 347, Yang St., Neihu Chiu, Taipei, Taiwan 11475		XMULTIPLE USA 543 Country Club Drive #B 128 Simi Valley, CA 93065		CUSTOMER/NO:	
THIS DRAWING IS A CONTROLLED DOCUMENT.					
TITLE: Stacked RJ45, Connectors, w/LED, 8P, 8C, Shielded, Thru Hole, 2 Piece Structure			DWG NO: XRJD-S-23-8-8-4		
PART NO: XRJD-S-23-8-8-4			DRAWN: EVA		
			CHKD: C. TSAI		
		DIMENSIONS	SHEET	REV	DATE: 06/10/03
		mm[inch]	1 of 1	A	