



SUGGESTED PCB LAYOUT  
TOP VIEW

DIMENSIONAL TOLERANCE: .XX ±0.08[0.003]

RoHS Compliant

NOTES:

- MATERIAL:  
HOUSING-PBT POLYESTER UL94V-0  
MIXED GLASS FIBER  
STANDARD COLOR-BALCK  
CONTACTS-0.45mm DIAMETER PHOS-BRONZE  
PLATED WITH 6u" GOLD.  
SHIELD-0.20mm THICK COPPER ALLOY,  
PLATED WITH NICKEL.
- OPERATING TEMPERATURE: -40°C ~ +85°C
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS  
PART 68,SUBPART F.
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]  
.X ±0.30[0.012]

XRJK-S-02-6-2-0-6F4-JU

PRODUCT SERIES LATCH DOWN THRU HOLE  
SHIELDED TYPE S = SHIELDED  
NO. OF PORTS  
NO. OF POSITION  
NO. OF CONTACT  
SERIAL NUMBER  
RUNNING CODE  
LED COLOR OPTION  
CUSTOMER CODE  
CONTACT GOLD PLATING OPTION

		THE INFORMATION AGE		
		XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475	XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	G/NO: 9697
THIS DRAWING IS A CONTROLLED DOCUMENT.				
TITLE:		RJ11 Connectors, w/D LED, 6P, 2C, Shielded, Thru-Hole		
PART NO:		XRJK-S-02-6-2-0-6F4-JU		
	UNIT	SHEET	REV	DATE:
	mm[inch]	1 of 1	01	Feb.18,08
		DWG NO:		CHKD:
		XRJK-S-02-6-2-0-6F4-JU		JEFF
		DRAWN:		
		LEDN		