



NOTES:

- MATERIALS:
HOUSING: HIGH TEMP. THERMOPLASTIC, PBT, UL 94V-0, BLACK
CONTACTS: T=0.35 mm PHOSPHOR BORNZE, 50μ' NICKEL UNDERPLATE
ON ALL AREA, 100μ' TIN ON TERMINATION END,
15μ' GOLD ON CONTACT AREA.
SHIELD: BRASS , NICKEL PLATING
- OPERATING TEMPERATURE: -40°C ~ +85°C
- JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68,
SUBPART F
- UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
.X ±0.30[0.012]

RoHS Compliant

XMULTIPLE		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: RJ45 Connectors, W/LED, 8P,8C, Shielded, Thru-Hole		DWG NO: XRJM-S-04-8-8-5-7G1	
PART NO: XRJM-S-04-8-8-5-7G1		DRAWN: TOM	
		UNIT	REVISION
		mm[Inch]	01
SHEET		DATE:	
1 of 1		Jun,20,07	