



SUGGESTED PCB LAYOUT
(TOP VIEW)

NOTES:

- 1. MATERIAL: HOUSING-PBT POLYESTER UL94V-0
MIXED GLASS FIBER.
STANDARD COLOR-GARY.
CONTACTS-0.45mm DIAMETER PHOS-BRONZE
PLATED WITH 6u" GOLD.
METAL PEG-0.50mm THICK PHOS-BRONZE
PLATED WITH TIN.
- 2. CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.
- 3. SOLDERING TEMPERATURE : 180°C
- 4. UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]
.X ±0.30[0.012]

RoHS Compliant

X MULTIPLE		CONNECTING THE INFORMATION AGE	
X MULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chu, Taipei, Taiwan 11475		X MULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO: 9674-6404-4	
TITLE: RJ11 Connectors, W/D LED, 6P,4C, Unshielded, Vertical Mount, Thru-Hole		DWG NO: XRJV-U-04-6-4-0-901	
PART NO: XRJV-U-04-6-4-0-901		DRAWN: TARA	
UNIT mm[inch]		CHKD: JEFF	
SHEET 1 of 1		DATE: Jan.04,06	
REV B			