



MATERIAL (RoHS COMPLIANT) -

1. CABLE:

CONDUCTOR: TWO TWISTED PAIRS,
28AWG SOLID SILVER PLATED COPPER.

INSULATION: FOAM POLYOLEFIN.

DIAMETER: 5.59mm NOMINAL. COLOR: BLACK.

DIFFERENTIAL IMPEDANCE: 100±5 OHMS @TDR

2. HOOD: ZINC DIE CASTING, NICKEL PLATING.

3. LATCH: ABS RESIN UL94V, COLOR IN BLACK.

4. P.C.B.: 4 LAYERS, FR4, 30U" GOLD

ON GOLDEN FINGERS, COLOR: RED.

5. SERIAL ID IC:

6. PASSIVE TYPE

7. FOR 2.5G

WIRING CHART			
P1 END		P2 END	
P1 PAD	SIGNAL	P1 PAD	SIGNAL
12	RX-	19	TX-
13	RX+	18	TX+
GROUND		GROUND	
18	TX+	13	RX+
19	TX-	12	RX-
GROUND		GROUND	

RoHS Compliant

SINGLE PORT

	CABLE LENGTH
①	500mm +/- 20mm
02	600mm +/- 20mm
03	1000mm +/- 20mm
04	2000mm +/- 40mm
05	3000mm +/- 40mm
06	4000mm +/- 40mm

<h1>X MULTIPLE</h1>		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE:		SFP 20P CABLE ASSMBLY	
PART NO:		XSFP-CB-PP2001	
	UNIT	SHEET	REV
	mm[inch]	1 of 1	01
DATE:		Nov.20,08	
G/NO:		DWG NO:	
		XSFP-CB-PP2001	
		DRAWN:	
		IVAN	
		CHKD:	
		TARA	