



NOTES:

- ELECTRICAL CHARACTERISTICS
 CONTACT CURRENT RATING: 1.5AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V AT SEA LEVEL.
 INSULATION RESISTANCE: 1000MEGOHMS MIN.
 CONTACT RESISTANCE: 30MILLIOHMS MAX.
 OPERATING TEMPERATURE: -55° C TO +85° C
- MECHANICAL CHARACTERISTICS
 MATING FORCE: 3.5KG. MAXIMUM.
 UNMATING FORCE: 1KG. MINIMUM.
- MATERIAL
 CONTACTS: COPPER ALLOY, GOLD FLASH PLATING.
 INSULATOR: PBT, WHITE
 SHELL: COPPER ALLOY, NICKEL PLATING
- UNSPECIFIED TOLERANCE: .XXX ±0.20
 .XX ±0.25
 .X ±0.30

XUSB-6-2-4-3-1-3-07

6 : USB
 2 : A/T RIGHT ANGLE DIP
 NUMBER OF PIN
 SHELL PLATING
 3 : ALL NI
 1 : GOLD FLASH
 SERIAL NUMBER
 HOUSING COLOR
 3 : WHITE
 PIN PLATING

RoHS Compliant

SUGGESTED PCB LAYOUT
 TOP VIEW
 DIMENSIONAL TOLERANCE: .XX ±0.08[0.003]

		THE INFORMATION AGE	
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE: USB-A Female 90D DIP		DWG NO: XUSB-6-2-4-3-1-3-07	
PART NO: XUSB-6-2-4-3-1-3-07		DRAWN: RUNES	
		UNIT: mm[inch]	SHEET: 1 of 1
		REV: 01	DATE: Feb.26,07
CHKD: JEFF		DATE: Feb.26,07	