

Part Numbering:

XRJH - XXX - X - X XX - X X X

NUMBER OF PORTS &
MECHANICAL TYPES
(SEE NOTE 1)

LED COLOR OPTIONS

PROTOCOL TYPES

D: 10/100 Mbps, 4 cores or 6 cores
E: 10/100 Mbps, 5 cores
H: 10/100/1000 Mbps, 8 cores
L: 10/100/1000 Mbps, 12 cores

CIRCUIT TYPES

LED POLARITY OPTIONS

0: Non-LED
1: + - , + -
2: + - , - +
3: - + , - +
4: Bi-color , Bi-color
5: Bi-color , + -
6: Bi-color , - +
7: + - , Bi-color
8: - + , Bi-color
9: Tri-color , Tri-color
A: Tri-color , + -
B: - + , + -

SPECIAL CODE OPTIONS

0: Standard
1: Operating Temperature
-40°C ~ +85°C
2: Exterior base covered with PCB
3: Contact gold plating 50u"
4: Housing material - Nylon
5: LED with resistance
6: HR1 R/R (contact pin right 1
solder pin right 1)
7: R/L (contact pin right 1
solder pin right 1)
8: Without Logo
9: Elecharacteristics follow
customer request
A: 8P10C→8P8C
PIN 1 & 10 eliminated
B: With Logo, w/o part number and
date code printed
C: Remove partial pins
D: LED with resistance;Housing
material - Nylon
F: LED - High Temp.
G: Pantone 299 Blue
H: LED use glue(KE45) to fix
J: Without Logo, but with date
code printed
S: PBT+15U"(Small size for Samsung)
Y: Pantone 114C Yellow

SHIELDING TYPES
(SEE NOTE 2)