



- MATERIALS:
HOUSING: HIGH TEMP. THERMOPLASTIC, BLACK, UL 94V-0
CONTACTS: 0.014 INCHES (0.35 MILLIMETERS) THICK PHOSPHOR BRONZE PLATED WITH 150 MICROINCHES (3.81 MICROMETERS) MINIMUM THICK TIN LEAD IN SOLDER AREA. 15 MICROINCHES (0.38 MICROMETERS) MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 50 MICROINCHES (1.27 MICROMETERS) MINIMUM THICK NICKEL.
SHIELDED: 0.0098 INCHES (0.25 MILLIMETERS) THICK COPPER ZINC ALLOY PLATED WITH 30 MICROINCHES (0.762 MICROMETERS) MINIMUM THICK NICKEL
- JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F
- PART NUMBER: XRJM-S-02-8-8-X
REFER TO LED OPTIONS TABLE FOR ORDERING CODES

NOTES: UNLESS OTHERWISE SPECIFIED
UNSPECIFIED TOLERANCE: .XX±0.010[0.25]
.X±0.006[0.15]

XMULTIPLE		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 2F, No. 60, Jhuhen St., Taipei 10488, Taiwan.		XMULTIPLE USA 3006 Old Connel Road Newbury Park, CA 91380	
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE: RJ45 Connectors, W/LED, SP, BC, Shielded, Thru-Hole		DRAWN: VIQ	
PART NO: XRJM-S-02-8-8-X-F1		CHK: C. TSAI	
DIMENSIONS mm [inch]		SHEET 1 of 1	
REV J1		DATE: 07/12/01	