



## Part Numbering

XUSB-6-04-9-1-1-01

- 1 : USB A TYPE SOLDER TYPE  
 2 : USB A TYPE DIP TYPE  
 3 : USB A TYPE RIGHT ANGLE DIP  
 4 : USB B TYPE SOLDER TYPE  
 5 : USB B TYPE DIP TYPE  
 6 : USB B TYPE RIGHT ANGLE DIP
- PIN No.  
 SHELL PLATING  
 1 : Ni AND Sn/Pb PLATING  
 2 : ALL Sn/Pb PLATING  
 3 : ALL Ni PLATING  
 4 : ALL Au PLATING  
 5 : ALL Zn PLATING  
 6 : ALL Ag PLATING
- INSULATOR COLOR  
 1 : BLACK 7 : RED  
 2 : BLUE 8 : VIOLET  
 3 : WHITE 9 : OTHER COLOR  
 4 : GRAY  
 5 : GREEN  
 6 : YELLOW
- PIN PLATING  
 1 : GOLD FLASH  
 2 : Sn/Pb PLATING  
 3 : ALL Au PLATING  
 4 : Au 5u" PLATING  
 5 : Au 15u" PLATING  
 6 : Au 30u" PLATING  
 7 : HALF Ni AND Sn/Pb PLATING  
 8 : ALL Au 30u" PLATING  
 9 : Ag PLATING
- RUNNING No.

## NOTES:

- ELECTRICAL CHARACTERISTICS:**  
 Contact Current Rating: 1 Amperes.  
 Dielectric Withstanding Voltage: AC 750 V r.m.s.  
 Insulation Resistance: 1000 Megohms Minimum at DC 500V.  
 Contact Resistance: 30 Milliohms Maximum.  
 Operating Temperature:  $-40^{\circ}\sim+60^{\circ}$
- MATERIALS:**  
 Contacts: Phosphor bronze  
 Insulator: PBT, UL 94V-0 Rated ,black.  
 Shell: Brass ,Copper alloy.
- PLATING:**  
 Contacts: Gold Flash Over Nickel Plated  
 Front Shell: Tin Plated Over Cu  
 Back Shell: Nickel Plated Over Cu

UNLESS OTHERWISE SPECIFIED  
 UNSPECIFIED TOLERANCE: .XX  $\pm 0.25[0.010]$   
 .X  $\pm 0.30[0.012]$

X MULTIPLE		CONNECTING THE INFORMATION AGE
XMULTIPLE ASIA 3F, No. 80, Juiwen St., Taichung, 104, Taiwan, R.O.C.	XMULTIPLE USA 3555 Old Conejo Road Newbury Park, CA 91320	G/NO:
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG NO: USB-00001
TITLE: USB B TYPE FEMALE RIGHT ANGLE		DRAWN: F.T. Chen
PART NO: XUSB-6-04-9-1-1-01		CHKD: C. TSAI
	DIMENSIONS	SHEET
mm[inch ]	1 of 1	REV
		DATE: 06/13/02