



BI-COLOR LED DETAIL
 (RED, RED/YELLOW, GREEN/ORANGE LED'S ARE ALSO AVAILABLE)

SUGGESTED PCB LAYOUT
 (COMPONENT SIDE)

PCB LAYOUT
 TOLERANCE
 .XX±0.05[0.002]

1. MATERIALS:
 HOUSING: HIGH TEMP. THERMOPLASTIC, BLACK, UL 94V-0
 CONTACTS: 0.014 INCHES (0.35 MILLIMETERS) THICK PHOSPHOR BRONZE PLATED WITH 150 MICROINCHES (3.81 MICROMETERS) MINIMUM THICK TIN LEAD IN SOLDER AREA. 15 MICROINCHES (0.38 MICROMETERS) MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 50 MICROINCHES (1.27 MICROMETERS) MINIMUM THICK NICKEL.
2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F
3. PART NUMBER: XRJ-U-01-8-8-X-F2

REFER TO LED OPTIONS TABLE FOR ORDERING CODES

NOTES:
 UNLESS OTHERWISE SPECIFIED
 UNSPECIFIED TOLERANCE: .XX±0.25[0.010]
 .X±0.30[0.012]

XMULTIPLE		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA OF No. 80, Andou St. Taipei, 104, Taiwan, R.O.C.	XMULTIPLE USA 5000 Old County Road Newbury Park, CA 91380	RMC	
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE: RJ45, Connectors, V/LED, 8P, 8C, UNshielded, Thru-Hole	DRAWN: VJQ		DWG NO: FDL01-802
PART NO: XRJM-U-01-8-8-X-F2	CHKD: C. TSAI		DATE: 10/06/01
DIMENSIONS mm[Inch]	SHEET 1 of 1	REV J	