


SUGGESTED PCB LAYOUT
(COMPONENT SIDE)



BI-COLOR LED DETAIL
(RED, RED/YELLOW, GREEN/ORANGE LED'S ARE ALSO AVAILABLE)

PCB LAYOUT
TOLERANCE
.XX±0.05[0.002]

1. MATERIALS:
HOUSING: HIGH TEMP. THERMOPLASTIC, BLACK, UL 94V-0
CONTACTS: 0.014 INCHES (0.35 MILLIMETERS) THICK PHOSPHOR BRONZE PLATED WITH 150 MICROINCHES (3.81 MICROMETERS) MINIMUM THICK TIN LEAD IN SOLDER AREA. 15 MICROINCHES (0.38 MICROMETERS) MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 50 MICROINCHES (1.27 MICROMETERS) MINIMUM THICK NICKEL.

2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F

3. PART NUMBER: XRJ-U-01-8-8-X-F2

REFER TO LED OPTIONS TABLE FOR ORDERING CODES

NOTES:

UNLESS OTHERWISE SPECIFIED
UNSPECIFIED TOLERANCE: .XX±0.25[0.010]
.X±0.30[0.012]

XMULTIPLE		CONNECTING THE INFORMATION AGE
XMULTIPLE AREA 247, P.O. BOX 100, TAIWAN ST. TAINAN, TAIWAN, R.O.C.	XMULTIPLE USA 3255 Old County Road Newbury Park, CA 91380	DATE: DWG NO: DRAWN: CHECKED: DATE:
THIS DRAWING IS A CONTROLLED DOCUMENT.		
TITLE: RJ45, Connectors, W/LED, 8P, 8C, UNshielded, Thru-Hole		
PART NO: XRJM-U-02-8-8-X-F2		
	DIMENSIONS	SHEET
mm [inch]	1 of 1	REV
		J
		DATE:
		10/06/01