



**MATERIAL:**

SHIELDED: 0.2mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.

HOUSING: PA6T C430NK UL-94V-0 STANDARD COLOR (BLACK).

INSERT: PA6T C430NK UL-94V-0,COLOR BLACK.

CONTACT: 0.35mm THICKNESS ALLOY C5210,  
GOLD PLATING OVER NICKEL IN CONTACT AREA.

TIN PLATING OVER NICKEL IN SOLDER AREA.

Gold Plating: Selective Gold Plating (6u",15u" ,30u" ,50u" AVAILABLE)

XMULTIPLE		COMMERCIAL PEOPLE TO PEOPLE
<small>XMULTIPLE ASIA 11F-13th Fl. Pre-Hing N. Road Taipei, Taiwan, R.O.C.</small>	<small>XMULTIPLE USA 3540 Old George Road Newbury Park, CA 91365</small>	DWG NO:
THIS DRAWING IS A CONTROLLED DOCUMENT.		989488-XRJSLP010
TITLE: RJ45 Jack, 8P, 8C, Shielded, SMT, Low Profile		DRAWN: VIQ
PART NO: XRJSLP-S-01-8-8-0	CHKD: C. TSAI	DATE: 11/06/00
	DIMENSIONS	SHEET
	inch [mm]	1 of 1
REV	A	